

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A blood purification device comprising:

a blood circuit having an arterial blood circuit and a venous blood circuit;

a blood pump disposed in said arterial blood circuit;

a blood purifier connected to the blood circuit between said arterial blood circuit and said venous blood circuit, and configured to purify blood flowing in said blood circuit;

a first measuring unit disposed in said arterial blood circuit and configured to measure a blood concentration of said arterial blood circuit;

a second measuring unit disposed in said venous blood circuit and configured to measure a blood concentration of said venous blood circuit;

a calculating unit configured to calculate a first measurement value and a first theoretical value, ~~[[the]]~~ said first measurement value referring to a ratio of said blood concentrations measured by said first measuring unit and said second measuring unit, and ~~[[the]]~~ said first theoretical value referring to a blood concentration ratio obtained by at least one formula based on parameters including a preset blood flow rate of said blood pump and a preset blood purifying rate of said blood purifier; ~~and~~

an evaluation unit configured to evaluate whether a difference between said first measurement value and said first theoretical value ~~are approximately equal~~ is larger than a predetermined acceptable ratio difference; ~~and~~

a reporting unit configured to report when the difference between said first measurement value and said first theoretical value is larger than the predetermined acceptable ratio difference,
wherein

~~said calculating unit performs a calculation in response to a result of evaluation by said evaluation unit to determine a performance of~~ when the difference between said first measurement value and said first theoretical value is larger than the predetermined acceptable ratio difference, the reporting unit reports a trouble condition for at least one of said blood pump and said blood purifier using ~~said at least one formula.~~

2. (Previously Presented) The blood purification device of claim 1, wherein:

said blood purifier includes a water removing unit connected to said blood purifier and configured to remove water from blood flowing in said blood purifier; and

said preset blood purifying rate is a preset water removal rate of said water removing unit.

3. (Previously Presented) The blood purification device of claim 2, further comprising:

a substitution fluid supplying unit configured to supply a substitution fluid into said blood circuit, wherein

said calculating unit configured to calculate a theoretical value referring to a ratio of the blood concentrations obtained by the at least one formula based on parameters including a preset substitution fluid supplying rate of said substitution fluid supplying unit and a filtration rate of said blood purifier in addition to said preset blood flow rate and said preset water removal rate.

4. - 7. (Canceled)

8. (New) The blood purification device of claim 1, wherein:

said blood pump is further configured to adjust the preset blood flow rate to an adjusted blood flow rate;

said calculation unit is further configured to calculate a second measurement value and a second theoretical value, the measurement value referring to a ratio of said blood concentrations measured by said first measuring unit and said second measuring unit while said blood pump is operated at said adjusted blood flow rate and said blood purifier is operated at said preset blood purifying rate, and the theoretical value referring to a blood concentration ratio obtained by at least one formula based on parameters including said adjusted blood flow rate of said blood pump and said preset blood purifying rate of said blood purifier;

said evaluation unit is further configured to evaluate whether said difference between said first measurement value and said first theoretical value is approximately equal to a difference between said second measurement value and said second theoretical value; and

said reporting unit is further configured to report the trouble condition for said blood purifier when said difference between said first measurement value and said first theoretical value is approximately equal to said difference between said second measurement value and said second theoretical value, and to report the trouble condition for said blood pump when said difference between said first measurement value and said first theoretical value is not approximately equal to said difference between said second measurement value and said second theoretical value.

